

HERONRIB

Hygienic, comfortable, self draining barefoot matting

The ultimate sports and leisure matting for use in wet areas where barefoot traffic is extensive.

Made from strong, non-porous PVC with channelled underbars, Heronrib will automatically self drain even the largest amounts of water. It is perfect to dissipate a splash while creating one with the many available attractive colours around swimming pools, saunas, jacuzzis and other wet areas using one or more of Heronrib's eye-catching colours.



BENEFITS

Certified slip resistance DIN 51097: C ASTM 1677: 0.9/0.7

4 way drainage

Excellent hygiene

Easy to cut and clean, contours to uneven surfaces

Quick to install

UV resistant

Fire resistant

Enhanced branding or styling

FEATURES

Embossed surface

Two layer construction and channelled underbars

Anti-microbial and anti-fungal additives

Made from flexible PVC

Supplied in 10m rolls

Can be used indoor or outdoor*

Certified EN 13501: Cfl - S1

6 standard colours

STANDARD COLOURS



OXFORD BLUE



OCEAN BLUE



CHARCOAL GREY



FOREST GREEN



MULBERRY RED*



WHITE

Other colours available on request.

* Mulberry Red colour is not colourfast in direct sunlight.

STANDARD SIZES

PRODUCT	FACTORY	HEIGHT	STANDARD ROLL OPTIONS**		
Heronrib	UK	10.5mm (13/32")	10 x 0.5m (33' x 1'8")	10 x 1m (33' x 3'3")	10 x 1.22m (33' x 4')
Heronrib	USA	10.5mm (13/32")	10 x 0.6m (33' x 2')	10 x 0.91m (33' x 3')	10 x 1.22m (33' x 4')

**Contact us for bespoke dimensions.





PRODUCT DATA SHEET: HERONRIB

Apr-17

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Height (mm)	Length (m)	Widths (cm)			Weight (kg/m ²)
<i>Tolerances (mm)</i>	<i>+/- 0.5</i>	<i>0+0.3</i>	<i>+/- 1</i>			
Heronrib	10.5	10	50	100	122	5.5



GENERAL

APPEARANCES	Open grid “duckboard” design with textured surface and castellated base bars.
COLOURS	Available in homogenous standard colours: Oxford Blue, Ocean Blue, Charcoal Grey, Forest Green, Mulberry Red and White. Red colour is not colourfast in direct sunlight. Other colours available on request. All on black base bars.
DURABILITY	One piece welded construction for maintenance free life.
WORKABILITY	Flexible construction is easy to cut and shape on site. Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.
USES	For poolside, changing rooms or where barefoot traffic is extensive, both inside or out.

TECHNICAL DATA

ACOUSTIC	Excellent sound absorption properties.
CHEMICAL	Resistant to most acids, alkalines and oils. For specific chemical resistances, see www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf
COMPOSITION	Flexible DINP plasticised Polyvinyl Chloride (PVC).
ENVIRONMENT	Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products. All PVC grid products are 100% recyclable. * Registration, Evaluation, Authorisation and Restriction of Chemical substances
FIRE	EN13501-1 : 2007 - Cfl - S1
HYGIENE	Non-porous 100% Virgin PVC - Inhibits the growth of bacteria. BPR (EU Biocidal Products Regulation 528/2012): Contains Biocidal Products for improved performance. Use Heronrib safely. Always read the label and product information before use. Anti-bacterial SteriTouch additive; Test JIS Z 2801:2000 – Determination of the antibacterial effect against: Staphylococcus aureus Result - Antimicrobial pass of >99% E. Coli Result - Antimicrobial pass of >99.99% Anti-fungal SteriTouch additive; Test method ASTM G21-09 - Determining resistance to fungi. Result - Nil Growth after 4 weeks
REVERSION	Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf
SLIP RESISTANCE	ASTM F 1677 - Dry/Wet: 0.9/0.7 DIN 51130: R11, V10
THERMAL	Functional -23°C +60°C (slight size variation may occur at temperature extremes).
UV LIGHT	Resistant to PVC degradation; uncoloured PVC material - BS EN 607 = Delta E 1.02 (Red colour is not colourfast in direct sunlight).
WARRANTY	3 years. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf

PRODUCT DATA SHEET: HERONRIB

ANCILLARIES



10mm x 50mm x 10.1m
(3/8" x 2" x 33')

50 PVC edging strip

Supplied in rolls of 10.1m (33') length
with cold welding paste.

Colours: Black, Dark Grey




10.5mm x 1.8m
(13/32" x 5'11")

Snap Track Low Profile

2 part snap track can be welded to join
rolls end to end or side to side for large area
covering. Supplied with cold welding paste.

Colour: Dark Grey



Connector clips - Dual purpose

For joining sections of matting together side
to side or end to end. Supplied in packs of 10.